FS 220 / FS 260 / FS 380

FOR FLOORS WITH SMALL INSTALL ATION HEIGHTS

MIGUTRANS

HEAVY-DUTY ALL-METAL JOINT SOLUTIONS FOR LARGE TRAFFIC LOADS



Symmetrical visible surface has no gaps avoids dirt accumulation

2 Striated surface ensures good skid resistance

3 Extremely flat, fixing without arms ideal for redevelopment, refurbishment, renovation

Articulated telescoping system absorbs movement in 3 directions

5 Solid all-metal expansion joint hard wearing, maintenance-free, long lasting

Expansion joint cover	Joint width max.	Total movement	Visible width	Total width	Joint height	Load bearing capacity	Load bearing capacity	Load bearing capacity
	bf [mm]	Δbf [mm]	b s [mm]	bt [mm]	h [mm]	[kN]	[kN]	solid plastic tyres [kg/mm]
FS 220/20	60	40 (±20)	220	220	21	600	130	15
FS 260/20	100	40 (±20)	260	260	21	600	130	15
FS 380/20	215	40 (±20)	378	378	21	300	70	15

Production length: 3 m **Standard colour:** Aluminium

We recommend fixing with Multi-Monti Stainless steel screws MMS F 7,5 x 95/30 ES (available ex stock), fixing distance: 200 mm.



